



- CZhonghu one hole conduit Clamp has an inverted rib providing more strength at the bend of the clip Snap-on
- feature leaves both hands free to work.

Applications:

Used to mount conduit systems flat against walls and other surfaces to provide extra support

Finish:

Blue Zinc Plated- 3-5 μ / Stainless Steel

Specification:

SAE J-429

Trade Size	Metric	Wall	Width	Hole	Inside	Quantity	Weight(kgs)
Inch	Designator	Thickness	mm	Diameter	Radius	Per Carton	Per Carton
1/2"	16	1.20mm	16.00mm \pm 0.20	6.00mm \pm 0.15	8.90mm	1500	10.71 \pm 2.00
3/4"	21	1.20mm	16.30mm \pm 0.20	6.00mm \pm 0.15	11.68mm	1200	13.32 \pm 2.00
1"	27	1.50mm	18.50mm \pm 0.20	6.00mm \pm 0.15	14.73mm	600	14.40 \pm 2.00
1-1/4"	35	1.50mm	22.20mm \pm 0.20	9.50mm \pm 0.15	19.05mm	300	15.39 \pm 2.00
1-1/2"	41	1.80mm	22.20mm \pm 0.20	9.50mm \pm 0.15	22.10mm	300	9.60 \pm 2.00
2"	53	1.80mm	22.20mm \pm 0.20	9.50mm \pm 0.15	27.94mm	200	8.40 \pm 2.00
2-1/2"	63	2.00mm	29.00mm \pm 1.00	10.00mm \pm 0.15	35.58mm	150	12.00 \pm 2.00
3"	78	2.00mm	29.00mm \pm 1.00	10.00mm \pm 0.15	43.80mm	80	10.28 \pm 2.00
3-1/2"	91	2.00mm	29.00mm \pm 1.00	10.00mm \pm 0.15	49.50mm	80	11.60 \pm 2.00
4"	103	2.00mm	29.00mm \pm 1.00	10.00mm \pm 0.15	56.60mm	60	10.20 \pm 2.00